



The WI-IP264-O is a full-color, day and night, outdoor camera with infrared illumination. It features a weatherproof housing and fog-resistant glass. The infrared lighting allows for illumination of objects as far away as 30 meters. The H.264 video compression ensures smooth, clean video.

The built-in web server allows users to control the camera via a web browser. Additionally, management software can be used for integrated surveillance and management of multiple network cameras. Ideal for banks, supermarkets, and office buildings.

VIDEO

Image Sensor	SONY 520 Line Super HAD CCD, NTSC/PAL	
Video Compression	H.264 Baseline Profile@Level 2.2	
Video Resolution	NTSC	352x240 (CIF), 704x240 (2CIF), 704x480(D1)
	PAL	352x288 (CIF), 704x288 (2CIF), 704x576(D1)
Video Settings	Brightness, Hue, Contrast, Saturation, Image Quality	
Video Frame Rate	NTSC	Up to 30 frames per second
	PAL	Up to 25 frames per second
Video Bitrate	Configurable between 16 kbps and 4 mbps	

AUDIO

Audio Input	1 channel, linear input
Audio Compression	G.726
Audio Output	1 channel, RCA interface, linear output
Audio Talk-Back	Built-in Microphone

NETWORK

Supported Protocols	TCP, UDP, IP, HTTP, FTP, SMTP, DHCP, DNS, ARP, ICMP, POP3, NTP, IPsec, UPNP, RTP, RTCP
System Interface	1 x RS485 port (supports transparent protocols)

PHYSICAL

Power Supply	DC 12V, 1A
Maximum Power	Less than 6 W
Operating Temperature	-10 ~ +55 deg. C
Operating Humidity	10 ~ 85% non-condensing