



Dimensions (L x W x H)

4.9 x 4.3 x 1.2 inches
125 x 108 x 30 mm

Weight

12.8 oz (350 g)

Our High-Power Indoor CPE radio can act as a multi-client bridge, access point or even a repeater. It is fully interoperable with IEEE 802.11b/g and features Power-over-Ethernet to allow for maximum flexibility when deciding where to place the radio. Plus, with multiple radios, seamless roaming allows users to travel between APs without losing their connection.

SPECIFICATIONS

Standard IEEE	802.11b/g, 802.1x, 802.3, 802.3u
Frequency Band	2400 --- 2484 MHz
Output Power/ Data Rates*	25dBm @ 1, 2, 5.5 and 11 Mbps 23dBm @ 6, 9, 12, and 18 Mbps 22dBm @ 24 and 36 Mbps 21dBm @ 48 and 54 Mbps
Receive Sensitivity (Typical)	-94dBm @ 1 Mbps -92dBm @ 2 Mbps -89dBm @ 5.5 Mbps -92dBm @ 6 Mbps -90dBm @ 9 Mbps -86dBm @ 11Mbps -88dBm @ 12 Mbps -86dBm @ 18 Mbps -83dBm @ 24 Mbps -79dBm @ 36 Mbps -74dBm @ 48 Mbps -72dBm @ 54 Mbps
Temperature Range	-10°C to 45°C - Operating -40°C to 70°C - Storage
Humidity (non-condensing)	5% to 95% typical